

ENDPOINT SOLUTIONS, LLC. CONFERRING SERVICES



Features:

Multipoint Conferencing
30 Frames Per Second
Point-to-Point Communication

Dial by Video Number
Multiple Inputs
Caller ID

Speed Dial
Privacy Button
Picture-in-Picture

Power	Power Consumption: 25 Watts Operating voltage (AC Adapter): 100-240 VAC, 50/60 Hz	Audio	G.711 at 56K/64K bps G.723.1 at 5.3K/6.4K bps Frequency Response: 50Hz -3.4kHz Electric Audio Volume Control Voice Activity Detection (VAD) Comfort Noise Generation Automatic Gain Control (AGC) Acoustic Echo Cancellation (AEC) Audio Input: Built-in High Sensitivity Microphone, Mic in Jack Audio Output: Earphone Jack, RCA Jack
Standards	System: H.323 Audio: G.711, G.723.1 Video: H.261, H.263	Remote Controller	Numerical keys: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, *, # Hot-Keys: View, Privacy, Still, Camera, Phonebook, In-Box, Out-Box, Mute Other Keys: <, >, ^, v, OK, CLEAR, On/Off Hook
Resolution	CIF (352 x 288 pixels) QCIF (176 x 144 pixels)		
Network Support	TCP/IP NAT PPPoE DHCP H.323 MCU Support H.323 Gatekeeper Support	Terminal Connections	RCA AV Input x 2 RCA AV Output x 1 RJ45 x1 Power x 1 Microphone Jack x 1
Build-In Camera	Illumination (min): 5 lux @ f1.8 Automatic Focus Range: 40 cm to Infinity Aiming Angle: 450 Auto Color and Brightness Auto Exposure and White Balance Artificial Lighting Flicker Reduction	Dimensions	24 cm (L) x 16 cm (W) x 6 cm (H)
Video	H.263 ITU-T Standard Frame Rate/Quality Selectable 4CIF Still Picture (VGA Quality) Local / Remote View or both View (Picture-in-Picture) Selectable Video Input: Built-in Camera or External Camera User Selectable Video Output: RCA Jack (NTSC or PAL)	Network Interface	RJ-45 Jack, 10 Base-T Ethernet

**THE FUTURE IS NOW – GET CONNECTED TODAY!
DON'T LET THE DISTANCE BETWEEN YOU KEEP YOU APART**

www.endpointolutions.net

973-696-0115

info@endpointolutions.net